

IN THE CLAIMS:

1. (Currently Amended) A method for accessing a device,

comprising:

 sending a resource access request to a device driver or OPROM

for the device;

 sending ~~an~~ a resource access command corresponding to the
~~device~~ resource access request from the device driver or OPROM to an
abstraction layer interface;

 verifying whether a resource operation corresponding to the
resource access command is authorized to be performed on the device;

 determining a resource access method(s) that may be implemented
to cause the device to perform the resource operation; and

 calling the resource access method(s) to perform the resource
operation on the device.

2. (Original) The method of claim 1, wherein the resource access
request comprises requesting data to be read from the device, further
comprising returning data read from the device to the device driver or
OPROM.

3. (Original) The method of claim 1, wherein the abstraction layer
interface includes a database from which resource access methods
corresponding to the device can be determined.

4. (Original) The method of claim 1, wherein the abstraction layer interface includes a database containing data corresponding to a configuration of a root bus to which the device is directly or indirectly connected to and resource information corresponding to any devices in a hierarchy of the root bus.

5. (Currently Amended) The method of claim 4, wherein the data corresponding to the root bus configuration and resources is represented by an object-oriented abstraction comprising a set of components that includes reference to one or more configuration methods that may be implemented to obtain and/or generate configuration and resource allocation information for the root bus and any devices and subordinate buses in the root bus hierarchy.

6. (Original) The method of claim 1, wherein the abstraction layer interface hides resource access methods for the device from the device driver or OPR0M so that the device driver or OPR0M may not directly access the device with those access methods.

7. (Currently Amended) A method for providing access to devices in a system that includes a plurality of root buses, comprising:

storing configuration and resource information corresponding to each of said plurality of root buses and any devices and subordinate buses in a hierarchy for that root bus;

providing an abstraction layer interface that enables device drivers and/or OPIROMs for the devices to perform resource operations on the devices through resource access methods corresponding to those devices, said abstraction layer hiding such resource access methods from the device drivers and/or OPIROMs so as to prevent the device drivers and/or OPIROMs from directly implementing the resource access methods to perform resource operations on their corresponding devices;

passing identification information and one or more resource access commands from a one or more of the device drivers and/or OPIROMs to the abstraction layer interface;

verifying whether a resource operation to be performed on a one of the devices, the one of the devices corresponding to said one or more resource access commands is authorized based on the identification information and the configuration and resource information that is stored; and

performing the resource operation on the device if it is authorized to be performed.

8. (Currently Amended) The method of claim 7, wherein the configuration and resource information for each root bus is represented as

an object-oriented abstraction comprising a set of components that includes reference to one or more configuration methods that may be implemented to obtain and/or generate configuration and resource information for the root bus and any devices and subordinate buses in the root bus hierarchy.

9. (Original) The method of claim 8, wherein the object-oriented abstractions for the root buses are stored in a database that is accessible by the abstraction layer interface.

10. (Original) The method of claim 9, further comprising providing a record for each device in the database identifying the device, a device driver or OPRM for the device, and the object-oriented abstraction corresponding to the root bus for the device.

11. (Original) The method of claim 7, further comprising publishing a public interface method that enables device drivers or OPRMs to access devices via the abstraction layer interface by passing identification, resource, and resource access command(s) to the abstraction interface.

12. (Original) An article of manufacture comprising a computer-readable medium having computer-executable instructions that when executed enable access to a device by performing the functions of:

sending a resource access request to a device driver or OPROM for the device;

sending ~~an~~ a resource access command corresponding to the resource access request from the driver to an abstraction layer interface;

verifying whether a resource operation corresponding to the resource access command is authorized to be performed on the device;

determining a resource access method(s) that may be implemented to cause the device to perform the resource operation; and

calling the resource access method(s) to perform the resource operation on the device

13. (Original) The article of manufacture of claim 12, wherein the resource access request comprises requesting data to be read from the device, and wherein execution of the instructions further performs the function of returning data read from the device to the device driver or OPROM.

14. (Original) The article of manufacture of claim 12, wherein execution of the instructions further performs the function of creating a database containing data corresponding to a configuration of a root bus to which the device is directly or indirectly connected to and resource information corresponding to any devices in a hierarchy of the root bus.

15. (Currently Amended) The article of manufacture of claim 9, wherein the data corresponding to the root bus configuration and resources is represented by an object-oriented abstraction comprising a set of components that includes reference to one or more configuration methods that may be implemented to obtain and/or generate configuration and resource allocation information for the root bus and any devices and subordinate buses in the root bus hierarchy.

16. (Original) The article of manufacture of claim 12, wherein the abstraction layer interface hides resource access methods for the device from the device driver or OPRM so that the device driver or OPRM may not directly access the device with those access methods.

17. (Original) An article of manufacture comprising a computer-readable medium having computer-executable instructions that when executed provide access to devices in a system that includes a plurality of root buses by performing the functions of:

storing configuration and resource information corresponding to each of said plurality of root buses and any devices and subordinate buses in a hierarchy for that root bus;

providing an abstraction layer interface that enables device drivers and/or OPRMs for the devices to perform resource operations on the devices through resource access methods corresponding to those

devices, said abstraction layer hiding such resource access methods from the device drivers and/or OPRoMs so as to prevent the device drivers and/or OPRoMs from directly implementing the resource access methods to perform resource operations on their corresponding devices;

passing identification information and one or more resource access commands from the device drivers and/or OPRoMs to the abstraction layer interface;

Q1 verifying whether a resource operation(s) to be performed on a device corresponding to said one or more resource access commands is authorized based on the identification information and the configuration and resource information that is stored; and

performing the resource operation on the device if it is authorized to be performed.

18. (Currently Amended) The article of manufacture of claim 17, wherein the configuration and resource information for each root bus is represented as an object-oriented abstraction comprising a set of components that includes reference to one or more configuration methods that may be implemented to obtain and/or generate configuration and resource information for the root bus and any devices and subordinate buses in the root bus hierarchy.

19. (Original) The article of manufacture of claim 18, wherein the object-oriented abstractions for the root buses are stored in a database that is accessible by the abstraction layer interface, and execution of the instructions further performs the function of providing a record for each device in the database identifying the device, a device driver or OPROM for the device, and the object-oriented abstraction corresponding to the root bus for the device.

20. (Currently Amended) A computer system comprising:
a memory in which a plurality of instructions are stored;
a device;
a root bus to which the device is operatively coupled; and
a processor connected to the root bus and the memory, said plurality of instructions when executed by the processor causing functions to be performed including:
sending a resource access request to a device driver or OPROM for the device;
sending ~~an~~ a resource access command corresponding to the resource access ~~command~~ request from the device driver or OPROM to an abstraction layer interface;
verifying whether a resource operation corresponding to the resource access command is authorized to be performed on the device;

determining a resource access method(s) that may be implemented to cause the device to perform the resource operation; and
calling the resource access method(s) to perform the resource operation on the device.

21. (Original) The system of claim 20, wherein the resource access request comprises requesting data to be read from the device, and wherein execution of the instructions further performs the function of returning data read from the device to the device driver or OPROM.

22. (Original) The system of claim 20, wherein execution of the instructions further performs the function of creating a database containing data corresponding to a configuration of a root bus to which the device is directly or indirectly connected to and resource information corresponding to any devices in a hierarchy of the root bus.

23. (Currently Amended) The system of claim 20, wherein the data corresponding to the root bus configuration and resources is represented by an object-oriented abstraction comprising a set of components that includes reference to one or more configuration methods that may be implemented to obtain and/or generate configuration and resource allocation information for the root bus and any devices and subordinate buses in the root bus hierarchy.

24. (Original) The system of claim 20, wherein the abstraction layer interface hides resource access methods for the device from the device driver or OPROM so that the device driver or OPROM may not directly access the device with those access methods.

25. (Original) A computer system comprising:
a memory in which a plurality of instructions are stored;
a plurality of root buses;
a plurality of devices connected to the root buses; and
a processor connected to the root buses and the memory, said plurality of instructions when executed by the processor causing functions to be performed including:

storing configuration and resource information corresponding to each of said plurality of root buses and any devices and subordinate buses in a hierarchy for that root bus;

providing an abstraction layer interface that enables device drivers and/or OPROMs for the devices to perform resource operations on the devices through resource access methods corresponding to those devices, said abstraction layer hiding such resource access methods from the device drivers and/or OPROMs so as to prevent the device drivers and/or OPROMs from directly implementing the resource access methods to perform resource operations on their corresponding devices;

passing identification information and resource access command(s) from device drivers and/or OPRoMs to the abstraction layer interface;

verifying whether a resource operation to be performed on a device corresponding to the resource access command(s) is authorized based on the identification information and the configuration and resource information that is stored; and

performing the resource operation on the device if it is authorized to be performed.

26. (Currently Amended) The system of claim 25, wherein the configuration and resource information for each root bus is represented as an object-oriented abstraction comprising a set of components that includes reference to one or more configuration methods that may be implemented to obtain and/or generate configuration and resource information for the root bus and any devices and subordinate buses in the root bus hierarchy.

27. (Original) The system of claim 26, wherein the object-oriented abstractions for the root buses are stored in a database that is accessible by the abstraction interface layer, and execution of the instructions further performs the function of providing a record for each device in the database identifying the device, a device driver or OPROM for the device, and the object-oriented abstraction corresponding to the root bus for the device.
